

PRODUCT INFORMATION SHEET

GOREME AGED LIMESTONE



GOREME AGED LIMESTONE

Hard wearing warm beige limestone with intricate calcite veins

Ageing process produces lightly worn texture, some open areas and subtle worn edge


Commercial and domestic projects

External paving and internal flooring

Harmonised Technical Specification EN12058:2004	
Name	Goreme Limestone
Petrography (EN12407)	Sedimentary Limestone
Description	Limestone with numerous fossils
Country of Origin	Turkey
Colour	Warm beige with darker areas and fossil
Finish	Aged
Apparent Density (EN1936)	2585kg/m
Open Porosity (EN1936)	2.42% vol
Compressive Strength (EN1926)	85.58MPa
Flexural Strength (EN12372)	16.01N/mm2
Abrasion Resistance (EN14157)	19.11mm
Frost Resistance (EN12371)	Frost Resistant



GOREME AGED LIMESTONE



Goreme Aged is a very hard wearing limestone which is suitable for use in commercial and residential projects. With low porosity and good frost resistance, Goreme can be used to create a seamless transition when used inside and out, and is suitable for use with under floor heating.

Goreme Limestone is quarried in central Turkey where numerous churches and chapels have been carved into the rock faces, dating back to the 9th Century.

Belvedere Stone

Belvedere Stone is part of the Lovell Stone Group, a family run company that is passionate about stone. The group own 5 quarries in the UK and produce building stone, architectural masonry, flooring and paving. We have used our expertise as Quarry Masters and Masons to source stone from quarries around the world with an undisputed heritage and proven resilience. Our masons have developed surface finishes for each stone to enhance their natural beauty.

For further information, please contact:

t: 03301359488

e: sales@belvederestone.com

w: www.belvederestone.com

